

General Engine Data			
Type	In-Line 4 cycle, water cooled, 6 Cylinder		
Aspiration	Turbocharged		
Cylinder Type	Replaceable dry liner		
Bore x Stroke	<i>mm (inch)</i>	111 x 139 (4.37 x 5.47)	
Displacement	<i>litre (inch<sup>3</sup>)</i>	8,071 (492.49)	
Compression Ratio	16.7 : 1		
Valves per Cylinder	- Intake	1	
	- Exhaust	1	
Valves lashes at cold	- Intake <i>mm (inch)</i>	0.30 (0.0118)	
	- Exhaust <i>mm (inch)</i>	0.30 (0.0118)	
Valve Timing	- Intake	Opening: 16° BTDC	Close: 36° ABDC
	- Exhaust	Opening: 46° BBDC	Close: 14° ATDC
Combustion Type	Direct Injection		
Firing Order	1-5-3-6-2-4		
Injection Timing	18° BTDC		
Rotation	Counter Clockwise, viewed from flywheel		
Dimension (L x W x H)	<i>mm</i>	1,264 x 899 x 1,453 (Construction Length – Height with Pedestal)	
Dry Weight	<i>Approx. kg (lb.)</i>	742 (1,636)	

Approved N Ratings	1,470 rpm	1,760 rpm	2,100 rpm	2,350 rpm
DF08TH-F Output <i>kW (hp)</i>	133 (178)	158 (212)	173 (232)	174 (233)

Fuel System			
Injection Pump	Zexel in-line "AD" type		
Governor	RSV type (all speed control)		
Feed Pump	Mechanical type		
Injection Nozzle	Multi hole type		
Opening Pressure	<i>kPa (psi)</i>	20,986 (3,043.8)	
Fuel Filter	Full flow, cartridge type		
Used Fuel	Diesel fuel type 2-D Only		
Fuel consumption	See table no. 03.100.06FCEN.XX		
Minimum Supply line Size	<i>mm (inch)</i>	10 (0.39)	
Minimum Return line Size	<i>mm (inch)</i>	10 (0.39)	

Electrical System		24 Volts (Nominal)	
Starter motor	<i>kW</i>	1 x 6	
Recommended Battery Capacity	<i>Ah</i>	150	
Quantity per battery bank	2		
Cold Cranking Amperes	<i>@ -18°C (0°F)</i>	950	
Charging Alternator Output	<i>Amps</i>	45	

Air Induction System			
Air Cleaner Type	Drip proof, Replaceable		
Engine Air Flow	<i>m<sup>3</sup>/min.</i>	15.3 @ 2,200 rpm	
Air Inlet Restriction Dirty	<i>kPa (mmH2O)</i>	6.2 (635)	
Air Inlet Restriction Clean	<i>kPa (mmH2O)</i>	2.2 (220)	

Cooling system		
Heat Exchanger Minimum Raw Water Flow		1 litre/Minute per kW installed
Engine Water Pump		Centrifugal type driven by belt
Water Pump Capacity	<i>litre/min. (gal./min.)</i>	270 (71) @ 2,450 rpm
Heat Exchanger Raw water Inlet		
Maximum Pressure	<i>kPa (psi)</i>	1,500 (217.6)
Flow	<i>litre/min. (gal./min.)</i>	174 (38.3)
Inlet Temperature	<i>°C (°F)</i>	37.8 (100)
Thermostat, Start to Open	<i>°C (°F)</i>	71 (160)
Fully Opened	<i>°C (°F)</i>	85 (185)
Coolant Capacity	<i>litre (gal.)</i>	21 (5.55)
Coolant Pressure Cap	<i>kPa (psi)</i>	95 (13.8)
Maximum Raw Water Supply pipe		Please Contact Manufacturer
Connection IN – OUT Heat Exchanger	<i>inch</i>	1 ½" BSP
Minimum Raw Water Pipe sizing		Please Contact Manufacturer
Raw water Ratio IN-OUT		OUT one size bigger than IN
Max. Engine Coolant Temperature	<i>°C (°F)</i>	96 (204.8)
Pressure loss Engine Cooling circuit	<i>kPa (psi)</i>	70 (10.2)

Lubrication System		
Lubricating Method		Fully Forced pressure feed type
Oil Pump		Gear type driven by crankshaft
Oil Filter		Full Flow, Cartridge type
Oil pressure Range, normal	<i>kPa (psi)</i>	100 (14.5) at idle 300-400 (43.5-58.0) at maximum speed
Max. Oil Sump Temperature	<i>°C (°F)</i>	95 (203)
Oil Sump Capacity High	<i>litre (gal.)</i>	15 (3.96)
Low	<i>litre (gal.)</i>	12 (3.17)
Total Engine Oil Capacity	<i>litre (gal.)</i>	15 (3.96)
Minimum Oil Pressure	<i>kPa (psi)</i>	75 (10.9)

Exhaust System		
Exhaust Gas Flow	<i>m<sup>3</sup>/min.</i>	10.3 @ 2,450 rpm
Exhaust Gas Temperature	<i>°C (°F)</i>	480 (896) @ 2,350 rpm
Max. Allowable Back Pressure	<i>kPa (mmH2O)</i>	9.8 (1,000)
Minimum Exhaust Pipe Diameter	<i>mm(inch)*</i>	87.9 (3")

\* Based on Nominal System. Flow analysis must be done to assure adherence to system limitations!

(Minimum exhaust pipe diameter is based on 15 feet of pipe, one elbow, and a silencer. Pressure drop no greater than one half the max. allowable back pressure)

Heater System		
Wattage (Nominal)	<i>W</i>	3,000
Voltage – AC	<i>V</i>	230

Engine Performance Data		
All data is based on the engine operating with fuel system, lubricating oil pump, air cleaner, and alternator; not included are compressor, fan, optional equipment, and driven components. Data is based on operation at SAE standard J1394 conditions of 300ft (91,4m) altitude, 29.61 in.(752mm) Hg dry barometer, and 77°F (25°C) intake air temperature, using No.2 diesel or a fuel corresponding to ASTM-D2.		
Altitude above which output should be Limited	<i>m (ft.)</i>	91.4 (300)
Correction Factor per 305m.(1,000ft.) above Altitude Limit		3%
Temperature above which output should be Limited	<i>°C (°F)</i>	25 (77)
Correction Factor per 11°C (10°F) above Temperature Limit		2% (1%)